


Nylon/Aluminium Butt Hinges



NYLON/ALUMINIUM BUTT

H I N G E S


This small range of butt hinges made from nylon and aluminium is specifically designed for those applications requiring moderate use whilst considering budget requirements.



1202 Nylon
With Stainless Steel Pin

LENGTH x WIDTH		KNUCKLE DIA MM	PIN DIA MM	LEAF THICKNESS MM	BOX UNIT PAIRS	BS CLASS	SCREW SIZE
INCHES	MM						
2 ¹ / ₂ x1 ¹¹ / ₁₆	64x43	9	4	4	10	-	6x3/4
3x1 ⁵ / ₁₆	76x49	9	4	4	10	-	8x1
4x2 ³ / ₈	102x60	10	4	5	5	-	8x1
4x2 ⁵ / ₈	102x67	13	4	6	5	-	10x1 ¹ / ₄

Finishes: Natural




1026 Aluminium Hinge Double Nylon Washered
With Stainless Steel Pin

LENGTH x WIDTH		KNUCKLE DIA MM	PIN DIA MM	LEAF THICKNESS MM	BOX UNIT PAIRS	BS CLASS	SCREW SIZE
INCHES	MM						
2 ¹ / ₂ x1 ³ / ₈	64x35	6	4	3	10	-	6x3/4
3x1 ⁵ / ₈	76x41*	6	4	3	10	3	8x1
3x2	76x51	9	5	3	10	6	8x1
4x2 ⁵ / ₈	102x67	11	5	4	5	7	10x1 ¹ / ₄
4x3	102x76	11	5	4	5	7	12x1 ¹ / ₄

Finishes: EA, PA

*Hinges have single nylon washers and stainless steel pin
Available polished and anodised only



1026 Aluminium Hinge Double Stainless Steel Washered
With Aluminium Pin

LENGTH x WIDTH		KNUCKLE DIA MM	PIN DIA MM	LEAF THICKNESS MM	BOX UNIT PAIRS	BS CLASS	SCREW SIZE
INCHES	MM						
3x2	76x51	9	5	3	10	6	8x1
4x2 ⁵ / ₈	102x67	11	5	4	5	8	10x1 ¹ / ₄
4x3	102x76	11	5	4	5	8	12x1 ¹ / ₄

Finishes: EA, PA

Technical Details

Material	Nylon 6:6 Aluminium HE 9
Pin	Aluminium 6060 T6 Stainless Steel 304 S15
Washers	Nylon 6:6 Stainless Steel 304 S15
Application	Suitable for internal application
Corrosion Resistance	Corrosion resistance from external damp conditions
Class 3	25,000 Cycles @ 20kg
Class 6	500,000 Cycles @ 40kg
Class 7	500,000 Cycles @ 60kg
Class 8	200,000 Cycles @ 80kg

Supplied by:

11/02